TECHNICAL PARAMETERS OF WATER HEATERS Parameters for the water heater and storage tank CTC FerroModul T-220 E7 Model(s): Conventional water heater: Heat pump water heater: No Solar water heater: No Back-up immersion heater: NA No Storage tank: General data Declared load profile XL Energy efficiency class **Energy efficiency** 38 % η_{WH} **4515** kWh Annual electricity consumption **AEC** Factory thermostat setting **60** °C **15** dB Sound power level indoors L_{WA} Q_{elec} 20.523 Daily electricity consumption kWh Fossil and/or biomass fuel heated water heater \mathbf{Q}_{fuel} Daily electricity consumption NA kWh NA Emissions of nitrogen oxides (dioxide) NO_{x} mg/kWh Solar heated water heater Collector aperture area m^2 A_{sol} Na Zero-loss efficiency η_{0} Na $W/(m^2 K)$ First-order coefficient Na a_1 Second-order coefficient Na $W/(m^2 K)$ a_2 Na Incidence angle modifier IAM Pump power consumption (solpump) Na W Standby power consumption (solstandby) Na W Heat pump heated water heater NA Sound power level outdoors dB L_{WA} Technical paremeter at declared load profile Storage water heater (3XS, XXS, XS) Volym Mixed vol 40° Storage water heater (S, M, XL, XXL, 3XL, 4XL) 320 L DHW Smart controller Weekly fuel consumption with smart kWh NA Q fuel, week, smart Weekly electricity consumption with smart Q elec, week, smart NA kWh NA kWh Weekly fuel consumption without smart Q fuel week Weekly electricity consumption without smart Q elec, week NA kWh Technical parameters for storagetank Storage volume V, C_{act} NA L

Specific precautions and end of life information:

Standing loss

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household

W

waste is not permitted.

Detailed Contact data: Enertech AB, Box 309, 341 26 Ljungby www.ctc.se