

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC AT 1. 750/50 6bar		
Conventional water heater:	No	Back-up immersion heater:	No
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes		

General data

Declared load profile	-	NA	-
Energy efficiency class	-	NA	-
Energy efficiency	η_{WH}	NA	%
Annual electricity consumption	AEC	NA	kWh
Factory thermostat setting	-	NA	°C
Sound power level indoors	L_{WA}	NA	dB
Daily electricity consumption	Q_{elec}	NA	kWh

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m ²
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m ² K)
Second-order coefficient	a_2	Na	W/(m ² K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Mixed vol 40° DHW	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Standing loss	S	127,0	W
Storage volume	V, C_{act}	678,0	L

F0134 211103

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Detailed Contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC AT 1.750/75 6bar		
Conventional water heater:	No	Back-up immersion heater:	No
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes		

General data

Declared load profile	-	NA	-
Energy efficiency class	-	NA	-
Energy efficiency	η_{WH}	NA	%
Annual electricity consumption	AEC	NA	kWh
Factory thermostat setting	-	NA	°C
Sound power level indoors	L_{WA}	NA	dB
Daily electricity consumption	Q_{elec}	NA	kWh

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m ²
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m ² K)
Second-order coefficient	a_2	Na	W/(m ² K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Mixed vol 40° DHW	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Standing loss	S	127,0	W
Storage volume	V, C_{act}	672,5	L

F0134 211103

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Detailed Contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC AT 2. 750 6bar		
Conventional water heater:	No	Back-up immersion heater:	No
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes		

General data

Declared load profile	-	NA	-
Energy efficiency class	-	NA	-
Energy efficiency	η_{WH}	NA	%
Annual electricity consumption	AEC	NA	kWh
Factory thermostat setting	-	NA	°C
Sound power level indoors	L_{WA}	NA	dB
Daily electricity consumption	Q_{elec}	NA	kWh

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m ²
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m ² K)
Second-order coefficient	a_2	Na	W/(m ² K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Mixed vol 40° DHW	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Standing loss	S	127,0	W
Storage volume	V, C_{act}	689,0	L

F0134 211103

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Detailed Contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC AT 1.750/50		
Conventional water heater:	No	Back-up immersion heater:	No
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes		

General data

Declared load profile	-	NA	-
Energy efficiency class	-	NA	-
Energy efficiency	η_{WH}	NA	%
Annual electricity consumption	AEC	NA	kWh
Factory thermostat setting	-	NA	°C
Sound power level indoors	L_{WA}	NA	dB
Daily electricity consumption	Q_{elec}	NA	kWh

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m ²
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m ² K)
Second-order coefficient	a_2	Na	W/(m ² K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Mixed vol 40° DHW	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Standing loss	S	127,0	W
Storage volume	V, C_{act}	710,0	L

F0134 211103

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Detailed Contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC AT 1. 750/75		
Conventional water heater:	No	Back-up immersion heater:	No
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes		

General data

Declared load profile	-	NA	-
Energy efficiency class	-	NA	-
Energy efficiency	η_{WH}	NA	%
Annual electricity consumption	AEC	NA	kWh
Factory thermostat setting	-	NA	°C
Sound power level indoors	L_{WA}	NA	dB
Daily electricity consumption	Q_{elec}	NA	kWh

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m ²
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m ² K)
Second-order coefficient	a_2	Na	W/(m ² K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Mixed vol 40° DHW	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Standing loss	S	127,0	W
Storage volume	V, C_{act}	704,5	L

F0134 211103

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Detailed Contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC AT 2. 750		
Conventional water heater:	No	Back-up immersion heater:	No
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes		

General data

Declared load profile	-	NA	-
Energy efficiency class	-	NA	-
Energy efficiency	η_{WH}	NA	%
Annual electricity consumption	AEC	NA	kWh
Factory thermostat setting	-	NA	°C
Sound power level indoors	L_{WA}	NA	dB
Daily electricity consumption	Q_{elec}	NA	kWh

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m ²
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m ² K)
Second-order coefficient	a_2	Na	W/(m ² K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Mixed vol 40° DHW	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Standing loss	S	127,0	W
Storage volume	V, C_{act}	721,0	L

F0134 211103

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Detailed Contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se